EM-120

Fully Automatic Chemistry Analyzer

Technical specifications

General information

Machine type: Random access, open reagent & locked

reagent (optional)

Test speed: Constant 120 tests/hour (Mono reagent

or double reagent)

Test principle: Colorimetric method,

turbidimetry

Test method: 1 point end, 2 point end,

Fixed-Time, Kinetics

Calibration type: Linear & nonlinear

Sample unit

Sample tray: 40 sample positions

Sample tube: Micro cup & test tube & blood

collection tube can be used. (<D 12-13)mm * (25-l00)mm

Sample volume: 2-30μL, step by 0.lμL

Sample probe: Liquid surface detection, timely tracking for liquid volume. Collision

Sample barcode Sample barcode reader (optional)

Reagent unit

Reagent tray: 80 reagent positions (40 for RI & 40 for R2),

Non-stop cooling system with peltier pad inside, 24 hours 2°C-14"C, open system,

could accept any reagent.

Reagent volume: $20-300\mu1$, step by $1\mu1$

Reagent needle: Liquid surface detection, timely tracking for

liquid volume. Collision avoidance.

Reagent barcode: Reagent barcode reader (optional)

Reaction unit

Reaction tray: 50 reaction cuvettes, new amorphous

optical plastics reaction cups, perfect

transmittance

Reaction volume: $150\mu1-330\mu1$ Reaction time: 10 minutes

Temperature: Peltier pad incubation system, reaction

temperature (37°C ± 0.1 "C)

Mixing system

Mixer: Paddle-type mixing, effective reducing

of carry-over

Optical system

Light source: Halogen lamp

340nm; 405nm; 450nm; 505nm; Wavelength:

546nm; 578nm; 630nm; 700nm

(4 more options)

Absorbance range: 0-4.0 Abs

Resolution: 0.0001 Abs

Operation system requirements

Operation Windows XP, Windows 7, Windows

system: 8, Windows 10

Data processing: Automatic calibration, test combi-

nation, effective time management of reagents, serum index, whole process detection, linear expansion of enzyme, blank deduction, dirty cuvette memory, cross infection prevention, patient information memory and association input, automatic report audit, data fuzzy query, report statistics and printing, reference range grading, alarm information classification, user operation privilege classification

management.

Report printing: 6 formats optional, surpport custom

Interface: TCP /IP network interface

Working conditions

Power supply: AC 110/220V ± 10%, 50/60 Hz, 650W

Water consumption: 6L/hour(maximum)

Dimension: 750mm * 550mm * 490mm(L *W*H)

Weight: 70kg

PRODUCT MANUFACTURED BY EASTMED

AN ISO9001;2008 CERTIFIED COMPANY













EM-120 Fully Automatic
Chemistry Analyzer >







EM-120

Fully Automatic Chemistry Analyzer

Multifunctional precision sampling probe



- External & internal mirror polish, external & internal probe washing
- Dedicated sampling probe equipped with sensitive liquid sensor, timely feedback of reagent & sample residuals
- Collision protection, automatic probe depth adjusting

Excellent mixer design



- Teflon coating mixer. No water dropping(reducing carry-over)
- Excellent mixing effect with standard mixing prosedure

High precision ceramic syringe



- Permanent ceramic piston
- Accurate dispensing as low as 0.1 μl

Reagent tray & Sample tray



- 80 reagent positions, 40 sample positions
- Non-stop cooling system with peltier pad inside, 24 hours 2°C-14°C
- Bar code reader(optional)

Reaction tray



- 50 reaction cuvettes
- Reaction volume as low as 150µ1
- Stable & accurate temperature (37±0.1 °C) for reaction

Advanced operating system



- User friendly software interface simple, easy-to-operate
- Sample automatic dilution(decrease, increase, normal)
- Reaction result automatic checking and warning, calibration result automatic checking, warning alarm log
- Linear & nonlinear calibration,-Multi-points calibration up to 8 points
- Quality control apply to westgard, L-T plot, cumulative

EM-120

Fully Automatic Chemistry Analyzer

Features

- Constant 120 test/ hour with double reagent
- 80 reagant positions
- Automatic liquid level sensing, anti-collision protection
- Integrated full closed optical system, multi-wavelength simultaneous detection
- New amorphous optical plastics reaction cups, perfect transmittance
- Maintenance free semiconductor solid state refrigeration
- Friendly surface and easy to operate

